



Recommended Installation Height
 From Floor to Top of Hand Dryer = 950mm
 From Floor to Bottom of Hand Dryer = 300mm
 Complies with Disabled Persons Requirements

Electrical Installation Options
 Simple electrical connection by plug and lead as supplied. Or can be direct wired by electrician.
 Visit website for detailed installation instructions

JET DRYER JD1000X [X = S (Silver), W (White), B (Blue), R (Red)]

TECHNICAL SPECIFICATIONS

Electrical

Input voltage :230-240V AC, Single Phase 50Hz
 Rated Power: 1200W, 5 Amp
 Motor Type : Vacuum, Brush Resistance Motor (Heat from motor is used to warm air)
 Energy Consumption per use : 0.0032 kWh
 Standby Power : 1 W

Construction

Polycarbonate – ABS Casing with antimicrobial additive to all external surfaces, Burn Proof
 Colour Finishes : Continental Silver, Grace White, Beach Blue, Crystal Red, Custom (Upon Request)
 Water Protection: IPX1

Filtration

Antibacterial coated PHMG Filter,
 Optional - HEPA Filter (96.8% @ 0.3)
 Optional - Phytoncide Aromatic Fragrance Gel Filter

Operation

Infra Red Touch Free Operation
 Hand Drying Time : Approx 10 - 15 Seconds
 Airflow: 300+ kph
 Operating Noise: Approx. 65 dba
 Water Holding Tank: 500ml
 Speed Control : User Speed Setting Switch

Weight

Unit Weight: 8kg
 Packaged Weight: 12kg

Warranty

3 year Parts, 1 Year Labour (Limited to 350,000 Uses)
 Optional Upgrade to 5 Years Parts

Product Certification

Approved to IEC/EN60335-1 and IEC/EN60335-2-23
 Compliant to EMC directive according to EN55014-1, EN55014-2, EN61000-3-2, EN61000-3-3 (CTICK N27284)

Ph: 1300 071 041

Email: info@jetdryer.com.au

Website: www.jetdryer.com.au

"The Faster Hygienic Hand Dryer"